

22" High Velocity Fan



YM-Yoke Mount Standard Mounting Options



PS- Pedestal Stroller



CW- Column Wall Mount



PB- Pedestal Base

Shipping Weights: 105 lbs/ 48 kg

91 lbs/ 41 kg

77 lbs/ 35 kg

SIZE	CFM	HP	FAN DIMENSIONS			DISTANCE AIR THROW	SHIPPING WEIGHT
			W	D	I.D.		
22"	5570	1/2	29"	16"	22 1/2"	100' / 30m	69 lbs/ 31 kg

Propeller: 20.75 "Diameter, 3 Blade GalvAlum (19 Degree)

Fan Inlet/Outlet: 16 Gauge Spun Steel

Finger Guards: OSHA STANDARD, Spiral Wound Steel

RPM: 1725

Decibels: 73.6 @ 20'

Enclosure: TEAO Standard

Frame: 56

Ambient Temperature: 40C

Duty Cycle: Continuous

Power Cord (115V Only): 12' Length

Coverage: 3600 Sq.Ft. Max

Warranty: 2 Years

Voltage

Motor
Amps

Running
Amps

115V/ 208-230V* 6.0/ 3.0-2.9 5.9/ 2.9-2.8

208-230/ 460V 2.4-2.3/ 1.2 2.3-2.2/ 1.1

277V 1.85 1.75

* Standard

22" High Velocity Fan Air Flow Pattern

